

## **AMENDMENTS TO THE CLAIMS**

This listing of claims will replace all prior versions, and listing, of claims in the application:

### **Listing of Claims**

1. (Currently amended): Trimmer head comprising at least two eyelets (17) and a bobbin (10) with at least two sections (11,12) for storing of one cutting filament (13,14) in each section, said eyelet (17) is placed in a housing surrounding the bobbin (10), characterized in that the eyelet (17) is provided with an opening (19) for the cutting filament, said opening (19) is extending in axial direction of the trimmer head so that the opening (19) provides access to all sections (11,12) for storing of cutting filaments (13,14), said opening (19) is ~~non-~~circular V-shaped having a first and a second end (21, 22), and that one side of the opening (19) has a groove shaped so that the cutting filament (13,14) is placed in the groove when the trimmer head rotates in the intended direction so that the cutting filament is placed in the groove by the forces generated by the rotation no matter of which section (11,12) of the bobbin (10) the filament (13,14) is stored in; wherein the V-shaped opening (19) of the eyelet (17) allows access to all sections (11, 12) to reload the cutting filament (13, 14) in such a way that the bobbin (10) is kept in the trimmer head during the reloading.

2. (Original) Trimmer head according to claim 1, characterized in that the eyelets (17) are placed around the same axial position on the trimmer head housing so that the cutting filaments (13, 14) will rotate in the same plane around the trimmer head.

3. (Currently Amended) Trimmer head according to claim 1, characterized in that the different sections (11, 12) of the bobbin (10) is separated by at least fragments of a wall (14 15) extending in radial direction from a cylindrical section (16) in the centre of the bobbin (10).

4. (Previously Presented) Trimmer head according to claim 3, characterized in that the cylindrical section (16) secures one end of the cutting filaments to the bobbin (10) in each of the different sections on the bobbin (10) for storing of one line of cutting filament in each section.

5. (Previously presented) Trimmer head according to claim 1, characterized in that the number of eyelets (17) at least is the same as the number of cutting filaments in the trimmer head.

6. (Original) Trimmer head according to claim 5, characterized in that the trimmer head comprises two eyelets (17) and two cutting filaments (13,14).

7-11. (Withdrawn)